PATENT ABSTRACTS OF JAPAN

(11)Publication number:

2002-269041

(43) Date of publication of application: 20.09.2002

(51)Int.Cl.

G06F 15/00 G06F 12/14 G06F 17/30 H04L 9/32

(21)Application number : 2001-066695

(71)Applicant : DAINIPPON PRINTING CO LTD

(22)Date of filing:

09.03.2001

(72)Inventor: YAGI NOBUHIRO


SUGIURA HIROAKI

(54) INFORMATION DISTRIBUTING SERVER DEVICE

(57) Abstract:

PROBLEM TO BE SOLVED: To provide an information distributing server device which can authenticate a user without depending on terminal environment and can manage the valid period of authentication in information service on the Internet.

SOLUTION: The device is provided with a request recording part recording a request from an authenticated user, a recording information monitoring part which periodically inspects the record of the request recording part and deletes expired record and an access control part which urges user authentication information when the accessed user is not authenticated and authenticates the user by collating information with management information which is previously registered if the user is authenticated and returns a requested content with respect to the authenticated request. The users are authenticated for the respective contents and the authenticated user is requested to be authenticated again when prescribed time elapses. Consequently, the user is authenticated with high safety without depending on the environment of a terminal unit.



* NOTICES *

JPO and INPIT are not responsible for any damages caused by the use of this translation.

- 1. This document has been translated by computer. So the translation may not reflect the original precisely.
- 2.**** shows the word which can not be translated.
- 3.In the drawings, any words are not translated.

CLAIMS

[Claim(s)]

JP-A-2002-269041 Page 2 of 6

[Claim 1] The request Records Department which is a server system for performing a data communications service, and records a request from an attested user on a personal digital assistant, The recorded information Monitoring Department which deletes record which inspected record of the request Records Department periodically and passed the term of validity, As opposed to a user who a request from a user is received, and the user inspects whether you are those by whom user authentication was already done with reference to said request Records Department, and has not been attested yet, Press for user authentication information, receive user authentication information, compare with management information registered a priori, and user authentication is performed, Thus, an access control section which returns as a response contents data demanded by receiving without a request by which user authentication was carried out, or a request from a user by which user authentication had already been carried out, If a user who performed user authentication for every ******** and contents, and once did user authentication also does fixed time lapse, by user authentication being required again. Information distribution server equipment characterized by a feasible thing without depending on environment of a terminal equipment for user access control whose safety is higher than mere user authentication.

[Claim 2] The request Records Department which is a server system for performing a data communications service, and records a request from an attested user on a personal digital assistant, The recorded information Monitoring Department which deletes record which inspected record of the request Records Department periodically and passed the term of validity, A request evaluating part in which the user inspects whether you are those by whom user authentication was already done with reference to said request Records Department about a user who has accessed, A user authentication treating part which presses for user authentication information, receives user authentication information to a user who has not been attested yet, compares with management information registered a priori, and performs user authentication, A delivery information generation part which prepares or creates contents which should be distributed to a user, An access control section which receives ****** and a request from a user and returns suitable contents data as a response, If a user who performed user authentication for every ***** and contents, and once did user authentication also does fixed time lapse, by user authentication being required again. Information distribution server equipment characterized by a feasible thing without depending on environment of a terminal equipment for user access control whose safety is higher than mere user authentication.

[Claim 3] Request record of one affair recorded on said request Records Department, The information distribution server equipment according to claim 1 or 2 which is a thing containing information which identifies demanded contents at least, information which identifies a user who has accessed and time when the request record was recorded, or a term when the request record is effective.

[Claim 4]Information which identifies a user who is recorded on said request Records Department, and who has accessed, By using terminal identification information automatically added to request messages after acting as intermediary when a gateway unit which a cellular phone business operator installs relays request messages which a user sends, The information distribution server equipment according to claim 3 making it unnecessary for a user to perform a user-authentication-information input on a personal digital assistant while request record to the contents concerned of the user concerned is effective.

[Translation done.]

* NOTICES *

JPO and INPIT are not responsible for any damages caused by the use of this translation.

1. This document has been translated by computer. So the translation may not reflect the original precisely.

mhtml:file://C:\Documents and Settings\rippg\Local Settings\Temp\wz54ba\Citation info\D... 3/8/2011

JP-A-2002-269041 Page 3 of 6

2.**** shows the word which can not be translated.

3.In the drawings, any words are not translated.

DETAILED DESCRIPTION

[Detailed Description of the Invention]

[0001]

[Field of the Invention]In personal digital assistant—oriented the information distribution system or data communications service using the Internet, this invention relates to the mechanism of making only a specific user doing inspection permission of the contents.

[0002]

[Description of the Prior Art]As for the distribute information which used the Internet today, it is common to build WWW (World Wide Web) technology as a base. The text file with a tag as which WWW technology expresses contents (it is henceforth described as a contents file), It can be said that it is realized in HTTP (HyperText Transfer Protocal) which is a communications protocol between the WWW server which sends out a contents file etc., the WWW browser which interprets and displays a contents file, and a WWW server and a WWW browser. As a contents file form, HTML (HyperText Markup Language) is typical.

[0003]When a WWW server provides the contents data which is having access restriction specified in the information distribution system using the WWW technology for [general] a cellular phone, Usually, a WWW server acquires required ID and password from the client terminal which requires ID and a password of a requesting agency, and requires service in advance of sending of contents data. This procedure is realized using the structure called the basic authentication function with which a WWW server is provided as standard in many cases.

[0004]In basic authentication, if the contents which are having access restriction specified are requested, a WWW server will be returned to status code of ANOSORAIZUDO request-origin. Then, the requested WWW browser displays the interface which enters user ID and a password, and sends the inputted user authentication information to a WWW server. A WWW server performs user authentication for received ID and the password with reference to a password management file. As a result, if it is checked that it is access from a registered user, the demanded contents data will be sent to a requesting agency. Since a WWW browser memorizes the entered user ID and the password, Henceforth, unless a browser is terminated by a client side, when the page concerned is accessed again and user authentication information is required again, the memorized user ID and the password are automatically sent to a server by work of a WWW browser. Namely, once it succeeds in user authentication, unless a browser will be terminated, a contents inspection of the server concerned is unconditionally possible for a client side.

[0005] With the spread of cellular phones, the Internet was accessed from the cellular phone and the service which provides a mobile phone user with information has also begun from the site on the Internet. In order to provide such service, a cell phone service entrepreneur provides the Gateway which mediates between a portable telephone communication network and the Internet, performs required protocol conversion on this Gateway, and is making data exchange. However, since the browser which a cellular phone carries has various restrictions, it does not support the abovementioned basic authentication in many cases.

[0006]

[Problem to be solved by the invention] There are two problems which are listed to below in the above—mentioned conventional technology. The first, I hear that user authentication using a basic authentication function function cannot be performed to what is not supporting a basic authentication function like the browser of a cellular phone, and it is. Since the second point will not be again attested unless a browser is terminated if attestation is finished at the time of first time access, I hear that others' illegal use etc. have a problem also in respect of security, and it has them. [0007] Let it be SUBJECT to provide the information distribution server equipment in which the attestation by which it is made in consideration of such a problem, and for which it does not depend on terminal environment is possible for this invention, and shelf-life management of attestation is

JP-A-2002-269041 Page 4 of 6

moreover possible.

[8000]

[Means for solving problem]In order to solve an aforementioned problem, the 1st mode of this invention, The request Records Department which is a server system for performing a data communications service, and records the request from an attested user on a personal digital assistant, The recorded information Monitoring Department which deletes the record which inspected record of the request Records Department periodically and passed the term of validity, As opposed to the user who the request from a user is received, and the user inspects whether you are those by whom user authentication was already done with reference to said request Records Department, and has not been attested yet, Press for user authentication information, receive user authentication information, compare with the management information registered a priori, and user authentication is performed, Thus, the access control section which returns as a response the contents data demanded by receiving without the request by which user authentication was carried out, or the request from a user by which user authentication had already been carried out, If the user who performed user authentication for every ****** and contents, and once did user authentication also does fixed time lapse, by user authentication being required again. It is information distribution server equipment characterized by a feasible thing without depending on the environment of a terminal equipment for the user access control whose safety is higher than mere user authentication.

[0009]When a person's request record by which user authentication was carried out is recorded on said request Records Department and said recorded information Monitoring Department deletes periodically the request record which passed the term of validity, Since user authentication will be again required if the user who once did user authentication also does fixed time lapse, it becomes possible to perform user access control whose safety is higher than mere user authentication. The request from a user by which user authentication is not carried out is received, Since it presses for user authentication information by work of an access control section by the server side and user authentication information is received, even when the personal digital assistant side does not support the basic authentication function of a WWW server, user authentication can be carried out without being dependent on the environment of a user's terminal equipment. * NOTICES *

JPO and INPIT are not responsible for any damages caused by the use of this translation.

- 1. This document has been translated by computer. So the translation may not reflect the original precisely.
- 2.**** shows the word which can not be translated.
- 3.In the drawings, any words are not translated.

DESCRIPTION OF DRAWINGS

[Brief Description of the Drawings]

[Drawing 1]It is an entire configuration figure of the information distribution server equipment 1.

[Drawing 2]It is a flow chart explaining operation of the access control section 10.

[Drawing 3]It is an operation flow figure of the recorded information Monitoring Department 21.

[Drawing 4] It is a figure showing the example of the request information recorded on the request Records Department 20.

[Explanations of letters or numerals]

- 1 Information distribution server equipment
- 7 Gateway
- 8 Portable telephone communication network
- 9 Internet
- 10 Access control section
- 11 Request evaluating part

JP-A-2002-269041 Page 5 of 6

- 12 Delivery information generation part
- 13 User authentication treating part
- 20 Request Records Department
- 21 Recorded information Monitoring Department
- 22 Access control file
- 30 Contents data storage part
- 90 Personal digital assistant


[Translation done.]


* NOTICES *

JPO and INPIT are not responsible for any damages caused by the use of this translation.


- 1. This document has been translated by computer. So the translation may not reflect the original precisely.
- 2.**** shows the word which can not be translated.
- 3.In the drawings, any words are not translated.

DRAWINGS






[Drawing 2]



[Drawing 4]



[Translation done.]

(19)日本国特許庁 (JP) (12) 公開特許公報 (A)

(11)特許出願公開番号 特開2002-269041 (P2002-269041A)

(43)公開日 平成14年9月20日(2002.9.20)

(51) Int.Cl. ⁷		識別記号		FΙ			รั	7]}*(参考)
G06F	15/00	3 3 0		G 0 6 F	15/00		330B	5B017
	12/14	320			12/14		320F	5B075
	17/30	110			17/30		110F	5 B 0 8 5
							110G	5 J 1 0 4
		1 2 0					120B	
			審查請求	未請求 諸	ず求項の数4	OL	(全 7 頁)	最終頁に続く

(21)出願番号 特願2001-66695(P2001-66695) (71) 出願人 000002897

大日本印刷株式会社 (22)出願日 平成13年3月9日(2001.3.9)

東京都新宿区市谷加賀町一丁目1番1号

(72)発明者 八木 伸公

東京都新宿区市谷加賀町一丁目1番1号

大日本印刷株式会社内

(72)発明者 杉浦 博昭

東京都新宿区市谷加賀町一丁目1番1号

大日本印刷株式会社内

(74)代理人 100111659

弁理士 金山 聡


最終頁に続く

(54) 【発明の名称】 情報配信サーバー装置

(57)【要約】

【課題】インターネット上の情報サービスにおいて、端 末環境に依存しないユーザ認証が可能で、しかも認証の 有効期間管理が可能な情報配信サーバー装置を提供する ことを課題とする。

【解決手段】認証済みユーザからのリクエストを記録す るリクエスト記録部と、リクエスト記録部の記録を定期 的に検査し有効期限を過ぎた記録を削除する記録情報監 視部と、アクセスしてきた利用者が未認証ユーザであれ ば、ユーザ認証情報を催促し、そうでなければ事前に登 録してある管理情報と照合してユーザ認証を行い、この ように認証されたリクエストに対して要求されたコンテ ンツを返信するアクセス制御部と、を備えて、コンテン ツ毎にユーザ認証を行い、かつ一旦ユーザ認証した利用 者も一定時間経過すると、再びユーザ認証を要求される ことで、安全性の高いユーザ認証を端末機器の環境に依 存せずに実施可能な情報配信サーバー装置により上記課 題を解決する。



【特許請求の範囲】

【請求項1】 携帯端末に情報配信サービスを行うため のサーバー装置であって、認証済みユーザからのリクエ ストを記録するリクエスト記録部と、リクエスト記録部 の記録を定期的に検査し有効期限を経過した記録を削除 する記録情報監視部と、利用者からのリクエストを受付 けて、前記リクエスト記録部を参照して、その利用者が 既にユーザ認証された者であるかを検査し、まだ認証さ れていない利用者に対しては、ユーザ認証情報を催促 し、ユーザ認証情報を受付け、事前に登録してある管理 10 情報と照合してユーザ認証を行い、このようにユーザ認 証されたリクエスト、または既にユーザ認証されていた ユーザからのリクエスト、に対して要求されたコンテン ツデータをレスポンスとして返すアクセス制御部と、を 備えて、コンテンツ毎にユーザ認証を行い、かつ一旦ユ ーザ認証した利用者も一定時間経過すると、再びユーザ 認証を要求されることで、単なるユーザ認証よりも安全 性の高いユーザアクセス制御を端末機器の環境に依存せ ずに実施可能なことを特徴とする情報配信サーバー装 置。

1

【請求項2】 携帯端末に情報配信サービスを行うため のサーバー装置であって、認証済みユーザからのリクエ ストを記録するリクエスト記録部と、リクエスト記録部 の記録を定期的に検査し有効期限を経過した記録を削除 する記録情報監視部と、アクセスしてきた利用者につい て、その利用者が既にユーザ認証された者であるかを前 記リクエスト記録部を参照して検査するリクエスト評価 部と、まだ認証されていない利用者に対しては、ユーザ 認証情報を催促し、ユーザ認証情報を受付け、事前に登 認証処理部と、利用者に配信すべきコンテンツを準備ま たは作成する配信情報生成部と、を備えて、利用者から のリクエストを受付けて適切なコンテンツデータをレス ポンスとして返すアクセス制御部と、を備えて、コンテ ンツ毎にユーザ認証を行い、かつ一旦ユーザ認証した利 用者も一定時間経過すると、再びユーザ認証を要求され ることで、単なるユーザ認証よりも安全性の高いユーザ アクセス制御を端末機器の環境に依存せずに実施可能な ことを特徴とする情報配信サーバー装置。

【請求項3】 前記リクエスト記録部に記録される1件 40 のリクエスト記録は、少なくとも、要求したコンテンツ を識別する情報、アクセスしてきた利用者を識別する情 報、および、そのリクエスト記録が記録された時刻また はそのリクエスト記録が有効な期限、を含むものである 請求項1または請求項2に記載の情報配信サーバー装 置。

【請求項4】 前記リクエスト記録部に記録されるアク セスしてきた利用者を識別する情報は、携帯電話事業者 の設置するゲートウエイ装置が、利用者の発信するリク

ッセージに自動的に付加する端末識別情報を利用するこ とにより、当該利用者の当該コンテンツへのリクエスト 記録が有効な間は、利用者が携帯端末上でユーザ認証情 報入力を行うことを不要としたことを特徴とする請求項 3に記載の情報配信サーバー装置。

【発明の詳細な説明】

[0001]

【発明の属する技術分野】本発明は、インターネットを 利用した携帯端末向けの情報配信システムあるいは情報 配信サービスにおいて、コンテンツを特定の利用者だけ に閲覧許可させる仕組みに関する。

[0002]

【従来技術】今日インターネットを利用した情報配信は WWW (World Wide Web) 技術をベースとして構築する ことが普通である。WWW技術は、コンテンツを表現す るタグ付きのテキストファイル(以後コンテンツファイ ルと記す)、コンテンツファイル等を送り出すWWWサ ーバー、コンテンツファイルを解釈し表示するWWWブ ラウザ、WWWサーバーとWWWブラウザ間の通信プロ トコルであるHTTP (HyperText Transfer Protoca 1) で成り立つといえる。コンテンツファイル形式とし てはHTML(HyperText Markup Language)が代表的

【0003】一般の、携帯電話を対象としないWWW技 術を用いた情報配信システムにおいて、WWWサーバー がアクセス制限を指定されているコンテンツデータを提 供する場合は、通常WWWサーバーは、コンテンツデー タの送付に先立ち、ID・パスワードをリクエスト元に 要求し、サービスを要求するクライアント端末から必要 録してある管理情報と照合してユーザ認証を行うユーザ 30 なID・パスワードを取得する。この手続きは、WWW サーバーが標準で備えるベーシック認証機能と呼ばれる 仕組みを用いて実現されることが多い。

【0004】ベーシック認証では、アクセス制限を指定 されているコンテンツがリクエストされるとWWWサーバ ーはアンオーソライズドのステイタスコードをリクエス ト元に返す。するとリクエストしたWWWブラウザはユ ーザID・パスワードを入力するインターフェースを表 示し、入力されたユーザ認証情報をWWWサーバーに送 る。WWWサーバーは受け取ったID・パスワードをパ スワード管理ファイルを参照してユーザー認証を行う。 この結果、登録済みユーザーからのアクセスであること が確認されれば、要求されたコンテンツデータをリクエ スト元に送付する。WWWブラウザは入力されたユーザ ID・パスワードを記憶するので、以後、クライアント 側でブラウザを終了させない限り、当該ページに再びア クセスして再度ユーザ認証情報を要求された時は、記憶 していたユーザ I D・パスワードをWWWブラウザの働 きにより自動的にサーバーに送付する。すなわち、一度 ユーザ認証に成功すれば、ブラウザを終了させない限 エストメッセージを中継する時に中継後のリクエストメ 50 り、クライアント側は無条件に当該サーバーのコンテン

ツ閲覧が可能である。

【0005】携帯電話の普及に伴い、携帯電話からイン ターネットに接続して、インターネット上のサイトから 携帯電話利用者に情報を提供するサービスも始まってい る。このようなサービスを提供するために携帯電話サー ビス事業者は、携帯電話通信網とインターネットを橋渡 しするゲートウエイを設けて、このゲートウエイの上で 必要なプロトコル変換を行ってデータのやり取りを行な わせている。しかしながら、携帯電話が搭載するブラウ ザは、様々な制約があるため上記ベーシック認証には対 10 応していないことが多い。

[0006]

【発明が解決しようとする課題】上記の従来技術では以 下に挙げるような二つの問題がある。その第一は、携帯 電話のブラウザのようなベーシック認証機能をサポート していないものに対しては、ベーシック認証機能を利用 したユーザー認証を行えないということである。また、 第二点は、初回アクセス時に認証を済ませると、ブラウ ザを終了させない限り再び認証されないので他人の不正 ある。

【0007】本発明はこのような問題点を考慮してなさ れたものであり、端末環境に依存しない認証が可能で、 しかも認証の有効期間管理が可能な情報配信サーバー装 置を提供することを課題とする。

[0008]

【課題を解決するための手段】上記課題を解決するた め、本発明の第1の態様は、携帯端末に情報配信サービ スを行うためのサーバー装置であって、認証済みユーザ からのリクエストを記録するリクエスト記録部と、リク エスト記録部の記録を定期的に検査し有効期限を経過し た記録を削除する記録情報監視部と、利用者からのリク エストを受付けて、前記リクエスト記録部を参照して、 その利用者が既にユーザ認証された者であるかを検査 し、まだ認証されていない利用者に対しては、ユーザ認 証情報を催促し、ユーザ認証情報を受付け、事前に登録 してある管理情報と照合してユーザ認証を行い、このよ うにユーザ認証されたリクエスト、または既にユーザ認 証されていたユーザからのリクエスト、に対して要求さ れたコンテンツデータをレスポンスとして返すアクセス 制御部と、を備えて、コンテンツ毎にユーザ認証を行 い、かつ一旦ユーザ認証した利用者も一定時間経過する と、再びユーザ認証を要求されることで、単なるユーザ 認証よりも安全性の高いユーザアクセス制御を端末機器 の環境に依存せずに実施可能なことを特徴とする情報配 信サーバー装置である。

【0009】前記リクエスト記録部に、ユーザ認証され た者のリクエスト記録を記録し、前記記録情報監視部が 有効期限を経過したリクエスト記録を定期的に削除する ことにより、一旦ユーザ認証した利用者も一定時間経過

すると、再びユーザ認証を要求されるので、単なるユー ザ認証よりも安全性の高いユーザアクセス制御を行うこ とが可能となる。また、ユーザ認証されていない利用者 からのリクエストに対しては、サーバー側でアクセス制 御部の働きによりユーザ認証情報を催促し、ユーザ認証 情報を受付けるので、携帯端末側がWWWサーバーのベ ーシック認証機能に対応していない場合でも、利用者の 端末機器の環境に依存せずにユーザ認証を実施すること ができる。

【0010】また、上記課題を解決するための、本発明 のより具体的な第2の態様は、携帯端末に情報配信サー ビスを行うためのサーバー装置であって、認証済みユー ザからのリクエストを記録するリクエスト記録部と、リ クエスト記録部の記録を定期的に検査し有効期限を経過 した記録を削除する記録情報監視部と、アクセスしてき た利用者について、その利用者が既にユーザ認証された 者であるかを前記リクエスト記録部を参照して検査する リクエスト評価部と、まだ認証されていない利用者に対 しては、ユーザ認証情報を催促し、ユーザ認証情報を受 利用などセキュリティー面でも問題があるということで 20 付け、事前に登録してある管理情報と照合してユーザ認 証を行うユーザ認証処理部と、利用者に配信すべきコン テンツを準備または作成する配信情報生成部と、を備え て、利用者からのリクエストを受付けて適切なコンテン ツデータをレスポンスとして返すアクセス制御部と、を 備えて、コンテンツ毎にユーザ認証を行い、かつ一旦ユ ーザ認証した利用者も一定時間経過すると、再びユーザ 認証を要求されることで、単なるユーザ認証よりも安全 性の高いユーザ認証を端末機器の環境に依存せずに実施 可能なことを特徴とする情報配信サーバー装置である。

【0011】本発明のさらに好ましい第3の態様として は、前記第1または第2の態様の情報配信サーバー装置 において、前記リクエスト記録部に記録される1件のリ クエスト記録は、少なくとも、要求したコンテンツを識 別する情報、アクセスしてきた利用者を識別する情報、 および、そのリクエスト記録が記録された時刻またはそ のリクエスト記録が有効な期限、を含むものである。

【0012】さらに好ましい態様としては、前記第3の 態様の情報配信サーバー装置において、前記リクエスト 記録部に記録されるアクセスしてきた利用者を識別する 情報は、携帯電話事業者の設置するゲートウエイ装置 が、利用者の発信するリクエストメッセージを中継する 時に中継後のリクエストメッセージに自動的に付加する 端末識別情報を利用することにより、当該利用者の当該 コンテンツへのリクエスト記録が有効な間は、利用者が 携帯端末上でユーザ認証情報入力を行うことを不要とし たものである。

【0013】ここで、端末識別情報は携帯電話事業者が 一定の条件で希望する利用者の携帯端末に与えるもので ある。従来のWWW技術におけるベーシック認証手段に おいては、一旦ユーザ認証を行った後は、WWWブラウ

ザがユーザID・パスワードを記憶し、以後のアクセスでは、WWWブラウザが自動的に記憶しているユーザIDをリクエストメッセージに付加するため、利用者は何度もユーザ認証情報を入力する必要がなかった。ところが、本発明の情報配信サーバー装置では、利用者端末側でそのような機能を前提としないため、一旦ユーザ認証した後の同一利用者からの再アクセスに対してどのように利用者を識別するかの問題点があった。そのリクエスト記録が有効な間であっても、アクセスする度にユーザ認証入力を行うのでは不便である。しかしこの問題は、上記のように、携帯電話事業者の設置するゲートウエイ装置が、利用者の発信するリクエストメッセージを中継する時に中継後のリクエストメッセージに自動的に付加する端末識別情報を利用することで解決した。

[0014]

【発明の実施の形態】以下、図面を用いて、本発明の好 適な実施形態である情報配信サーバー装置1を説明して ゆく。図1は、情報配信サーバー装置1 (以下サーバー 装置1)の全体構成図である。サーバー装置1は、アク セス制御部10、リクエスト記録部20、記録情報監視 部21、コンテンツ毎にアクセス可能なユーザを記録し たアクセス管理ファイル22、および、コンテンツデー タ記憶部30から構成される。サーバー装置1は、イン ターネット9と、インターネット9と携帯電話通信網8 とを接続するゲートウエイ7を通じて、利用者の使用す る携帯端末90とコンテンツデータおよびメッセージの やり取りを行う。サーバー装置1と携帯電話事業者が設 置するゲートウエイ7は、HTTP (HyperText Transf er Protocol) によりリクエストとレスポンスのメッセ ージをやり取りする。尚、以下の記載ではHTTPによ 30 るリクエストメッセージおよびレスポンスメッセージ を、それぞれHTTPリクエスト、HTTPレスポンス と略記する。

【0015】携帯端末90は、コンテンツファイルを解釈して表示するラウザを搭載した携帯電話等であって、サーバー装置1に対してクライアント端末として機能する。携帯端末90は各々固有の端末識別情報を有することを前提とする。端末識別情報は携帯電話事業者が一定の条件で希望する利用者の携帯端末に与えるものである。携帯端末90は携帯通信モジュールを接続したパソ 40コンやPDA等の携帯端末でもよい。

【0016】アクセス制御部10は、ユーザからのリクエストメッセージを受け付け、幾つかの必要な処理を実行し、最終的にリクエストに応じた結果を応答メッセージにしてユーザに返すよう働く。アクセス制御部10には、リクエスト評価部11、配信情報生成部12、ユーザ認証処理部13が内蔵されている。アクセス制御部10は、具体的には、HTTPリクエストを受け付け、リクエストに応じた結果を応答メッセージにしてユーザに返すWWWサーバソフトウエアとこのWWWサーバから

呼出される幾つかのソフトウエアプログラムで実現できる。

【0017】リクエスト評価部11は、アクセス制御部10が受付けたHTTPリクエストのリクエストURI (Uniform Resource Identifier) と端末IDが、後述するリクエスト記録部20に記録されているかどうかの判定を行う。URIはコンテンツを指定する識別情報である。リクエスト記録部20の情報は参照のみ行う。

【0018】リクエスト記録部20は、ユーザー認証後 10 のリクエスト情報、すなわちリクエストURIと端末I Dが、その有効期限とともに記録される。

【0019】ユーザー認証処理部13は、リクエスト評 価部11の判定の結果、リクエスト情報が記録されてい なかった時に起動され、受付けたリクエストに対してユ ーザー認証行う。すなわち、ユーザID·パスワードを 要求する対話インターフェースを生成するデータをリク エスト元に送出し、アクセスしてきた利用者に、設定さ れているユーザID・パスワードの入力を促す。 そして 返答結果を受取りコンテンツ毎に用意されているアクセ ス管理ファイル22を参照して、入力されたユーザID ・パスワードが当該コンテンツのアクセス管理ファイル 22に設定されているかどうか検査する。アクセス管理 ファイル22内に一致するユーザID・パスワードがあ れば、認証がなされたことになる。ユーザ認証処理部1 3は、現在時刻にアクセス管理ファイル22に記載され ている当該コンテンツの認証後有効時間を加えた時刻を 有効期限の時刻として算出し、リクエストされたURI と当該ユーザの端末IDとこの有効期限をリクエスト情 報としてリクエスト記録部20に記録する。そして、配 信情報生成部12に処理を促す。図4にリクエスト情報 の記録内容例を示す。

【0020】配信情報生成部12は、指定されたURIに従って表示するコンテンツを生成する。実際には、コンテンツを生成するプログラム、または、様々な素材データとのリンクを含むコンテンツファイルである。

【0021】記録情報監視部21は、リクエスト情報の時間管理を行う。登録されているリクエスト情報が有効期間を超えている場合はその情報を抹消する。

【0022】コンテンツデータ記憶部30は、配信用のコンテンツファイル及び素材データを記録格納するハードディスク等のメモリである。

【0023】図2はサーバー装置1の主要部であるアクセス制御部10の処理の流れを示すフロー図である。図2に従って、サーバー装置1が利用者からのコンテンツリクエストメッセージを受けてからコンテンツデータをレスポンスとして返すまでの処理フローを説明する。

【0024】アクセス制御部10はHTTPリクエストを受け取ると、リクエストURIと端末IDをリクエスト情報として抽出し(S10)、リクエスト評価部11 50 を呼出す。リクエスト評価部11は、抽出したリクエス

ト情報がリクエスト情報記録部2に記録済みかどうか検 査する(S15)。記録済みの場合、ユーザー認証処理 は行わずに配信情報生成部12に処理を促す(S4 0)。未記録の場合はユーザ認証処理部13に処理を促 す。

【0025】ユーザ認証処理部13は、クライアント端 末にID・パスワード入力ウインドウを表示させるデー タを送出し、アクセスしてきた利用者にID・パスワー ドの入力を促す(S25)。利用者によって入力された セス管理ファイル22に記録されているID・パスワー ドを照合し(S30)、一致していたらリクエスト情報 記録部20に、現在時刻とリクエスト情報を記録し(S 35)、配信情報生成部12に処理を促す(S40)。 一致していなかったらステップS25に戻る。

【0026】配信情報生成部12で、生成または既存の ファイルを読み出すことにより準備されたデータはHT TPレスポンスを構成してリクエスト元のクライアント 端末へ返信される(S45)。以上がリクエストメッセ ージを受付けてから応答を返すまでのアクセス制御部1 20 0の動作である。

【0027】リクエストURIとHTTPリクエストに 付加される端末IDがリクエスト記録部20にリクエス ト情報として記録される。リクエスト情報の有効期間は サービス毎にまたはコンテンツ毎に設定されている。有 効期間を越えた場合、リクエスト情報記録装置の記録内 容は全て無効となる(削除される)。有効期間を越えて リクエストを受け取った場合は、リクエスト元に対して 初回アクセスとしてユーザー認証情報を要求する。

【0028】次に記録情報監視部21の働きを述べる。 図3は、記録情報監視部21の動作フロー図である。記 録情報監視部21は定期的にリクエスト記録部を参照 し、有効期限を超過したリクエスト情報があるかどうか 検査する(S60)。有効期限を超過したリクエスト記 録を見つけた場合は、そのリクエスト記録を抹消する $(S70)_{a}$ * *【0029】以上、利用者へのアクセス制限手段に特徴 がある情報配信サーバー装置1を詳しく説明した。

[0030]

【発明の効果】本発明による情報配信サーバー装置によ れば、クライアント側でベーシック認証機能をサポート していない場合でも、ベーシック認証と同等の機能を提 供することが可能となるため、携帯端末をクライアント として用いる情報配信システムを構築する際、または携 帯端末向けの情報配信サービスを提供する際、携帯端末 ID・パスワードとコンテンツ毎に設定されているアク 10 の仕様の違いを考慮する必要がなく大変便利である。ま た、ベーシック認証と比べると、コンテンツの有効期限 管理が行える為、期間限定の配信サービスが可能となる という顕著な効果を奏することができる。

【図面の簡単な説明】

【図1】 情報配信サーバー装置1の全体構成図であ る。

【図2】 アクセス制御部10の動作を説明するフロー チャートである。


【図3】 記録情報監視部21の動作フロー図である。

【図4】 リクエスト記録部20に記録されるリクエス ト情報の例を示す図である。


【符号の説明】

- 情報配信サーバー装置 1
- ゲートウエイ 7
- 携帯電話通信網 8
- 9 インターネット
- 1.0 アクセス制御部
- リクエスト評価部 1 1
- 配信情報生成部 1 2
- 30 13 ユーザ認証処理部
 - 20 リクエスト記録部
 - 2 1 記録情報監視部
 - アクセス管理ファイル 2 2
 - 3 0 コンテンツデータ記憶部
 - 90 携帯端末


【図3】




【図1】



[図2]



[図4]



フロントページの続き

(51) Int. Cl. ⁷ 識別記号

FΙ

テーマコード(参考)

H O 4 L 9/32

H O 4 L 9/00 6 7 3 A

Fターム(参考) 5B017 AA06 BA05 BB09 BB10 CA16

5B075 KK43 KK54 KK63 PQ05 PR03 5B085 AA08 AE02 AE03 BA06 BC01

5J104 AA07 KA01 NA05 PA02